

FAX-T104 FAX-T106

A small, stylish machine with advanced business functions as standard, plus an integral telephone.

The FAX-T104 has been built with efficiency at the forefront stored in one-touch dial facility and there is speed dialling

Accepting up to 30 sheets of standard A4 paper together



FAX-T104 is both quick and easy to select any of the advanced business features - including the ability to send the same fax message to a number of recipients simultaneously, saving time and effort.

option to reduce or enlarge documents from 50-150%.

All the professional quality you expect built into a compact and stylish machine that is ideal for the small office or home

† ITU-T-Test Chart No. 1, Out of Paper Reception, ECM Mode.

Contact:

FAX-T104 **FAX-T106**

Technical Specifications

General

Plain paper thermal transfer fax 10 sheet auto document feeder (ADF) 30 sheet paper capacity Up to 25 pages out of paper reception[†] LCD display of 16 characters on 1 line On screen programming - prompts displayed within the LCD Automatic recognition of fax & telephone reception

Telephone

Integrated telephone handset Integrated speaker for 'On-Hook Dialling' (T106 only) On hold background music 4 one-touch dials 100 speed dials

Digital Answering MachineElectronic 'Message Manager' facility for faxes and voicemail Answering machine recording time up to 15 minutes (T106 only) Out-going message up to 20 seconds

9,600 bps Modem /T106 (Modem 14,400kbps) 15 second transmission speed, 9 second (T106) Group 3 ITU-T group compatibility Automatic redial

Transmission lock to prevent unauthorised access and transmission

Caller ID*, allows you to see the name or number of the caller (available for SPA/ GER/ FRA/ AUS/ UK/ IRE/ NOR/ SWE/ DEN/ BEL/ POR/ ITA/ HOL) ECM, Error Correction Mode will automatically detect errors during transmission and resend relevant pages. (Where both machines share ECM feature) Transmission verification report Super fine transmission

64-level greyscale

Advanced fax features: Broadcasting /Polling /Group dialling / Next fax reservation / Call reservation / Delayed transmission / Remote activation /Fax forwarding /Remote retrieval /Electronic cover page

Copy

Up to 99 multiple copies of each page loaded in the ADF Reduce or increase document sizes from 50% to 150%

Additional Features

Help list of basic operational steps and functions TAD interface for connecting external telephone devices

Weights and Measures

Power consumption: standby under 4.4W, peak 160W Dimensions (WxDxH): 302mm x 267mm x 340mm Weight 2.7kg

Consumables

PC-74RF, 4 x 144 sheet ribbon

PC-75, 1 x cassette including 144 sheet ribbon PC-71RF, 1 x 144 sheet ribbon PC-72RF, 2 x 144 sheet ribbon

* Purchased from the telephone company

NESOLUTION SERVIN

SVIS

short



Brother International Corp Ireland

Boeing Road, Airways Industrial Estate, Santry, Dublin 17 Tel:+353(0)1-241 1900 Fax:+353(0)1-842 4666 Email: sales@brother.ie Web-site: www.brother.com

ns correct at time of printing. Brother is a registered trademark of Brother Industries Ltd. Brand product names are registered trademarks or trademarks of their respective companies