

## TD-2D range

### Labelling solutions built for real work

Brother's range of TD professional label printers offer the ability to print high quality labels on demand while bridging the gap between full desktop and portable printing.

Brother's range of TD professional label printers offer the ability to print high quality labels on demand to meet your organisation's needs. Printing labels up to 4 inches in width, and with direct thermal and thermal transfer print technology, they fit the requirements of a large range of vertical market applications.

#### The desktop printer range at a glance...

2 inch desktop label, receipt and  
wristband printer



Direct thermal print technology  
Print width of up to 59mm  
Print speeds up to 152mm/sec (6ips)  
203dpi print resolution  
USB (Type C) and Serial\* connectivity  
P-touch Template, ESC/P, Raster and  
ZPL 2, EPL 2, DPL, CPCL emulations supported

**TD-2310D203**

2 inch desktop label, receipt and wristband  
printer with customisation options



Direct thermal print technology  
Print width of up to 59mm  
Print speeds up to 152mm/sec (6ips)  
203dpi print resolution  
USB (Type C), USB Host, Serial\* and  
Wired LAN connectivity  
P-touch Template, ESC/P, Raster and  
ZPL 2, EPL 2, DPL, CPCL emulations supported  
Rechargeable battery base unit available

**TD-2320D203**

High resolution 2 inch desktop label,  
receipt and wristband printer with  
customisation options



Direct thermal print technology  
Print width of up to 59mm  
Print speeds up to 152mm/sec (6ips)  
300dpi print resolution  
USB (Type C), USB Host, Serial\* and  
Wired LAN connectivity  
P-touch Template, ESC/P, Raster and  
ZPL 2, EPL 2, DPL, CPCL emulations supported  
Rechargeable battery base unit available

**TD-2320D300**

2 inch desktop label, receipt and  
wristband printer with full connectivity  
and customisation



Direct thermal print technology  
Print width of up to 59mm  
Print speeds up to 152mm/sec (6ips)  
203dpi print resolution  
USB (Type C), USB Host, Serial\* Bluetooth,  
Wired LAN and WiFi connectivity  
P-touch Template, ESC/P, Raster and  
ZPL 2, EPL 2, DPL, CPCL emulations supported  
Rechargeable battery base unit available

**TD-2350D203**

## TD-2D range continued

High resolution 2 inch desktop label, receipt and wristband printer with full connectivity and customisation



Direct thermal print technology

Print width of up to 59mm

Print speeds up to 152mm/sec (6ips)

300dpi print resolution

USB (Type C), USB Host, Serial\* Bluetooth, Wired LAN and WiFi connectivity

P-touch Template, ESC/P, Raster and ZPL 2, EPL 2, DPL, CPCL emulations supported

Rechargeable battery base unit available

**TD-2350D300**

2 inch desktop label, receipt and wristband printer with touch screen display



Direct thermal print technology

Print width of up to 59mm

Print speeds up to 152mm/sec (6ips)

203dpi print resolution

USB (Type C), USB Host, Serial\* and Wired LAN connectivity

P-touch Template, ESC/P, Raster and ZPL 2, EPL 2, DPL, CPCL emulations supported

Rechargeable battery base unit available

**TD-2320DSA203**

High resolution 2 inch desktop label, receipt and wristband printer with touch screen display



Direct thermal print technology

Print width of up to 59mm

Print speeds up to 152mm/sec (6ips)

300dpi print resolution

USB (Type C), USB Host, Serial\* and Wired LAN connectivity

P-touch Template, ESC/P, Raster and ZPL 2, EPL 2, DPL, CPCL emulations supported

Rechargeable battery base unit available

**TD-2320DSA300**

2 inch desktop label, receipt and wristband printer with full connectivity and touch screen display



Direct thermal print technology

Print width of up to 59mm

Print speeds up to 152mm/sec (6ips)

203dpi print resolution

USB (Type C), USB Host, Serial\* Bluetooth, Wired LAN and WiFi connectivity

P-touch Template, ESC/P, Raster and ZPL 2, EPL 2, DPL, CPCL emulations supported

Rechargeable battery base unit available

**TD-2350DSA203**

High resolution 2 inch desktop label, receipt and wristband printer with full connectivity, touch screen display and carry handle



Direct thermal print technology

Print width of up to 59mm

Print speeds up to 152mm/sec (6ips)

300dpi print resolution

USB (Type C), USB Host, Serial\* Bluetooth, Wired LAN and WiFi connectivity

P-touch Template, ESC/P, Raster and ZPL 2, EPL 2, DPL, CPCL emulations supported

Rechargeable battery base unit available

**TD-2350DSA300**

## TD-4D range

Versatile, high-resolution desktop printers for professional label printing.

4 inch direct thermal desktop  
printer



Direct thermal print technology  
Print width of up to 104.1mm  
Print speeds up to 127mm/sec (5ips)  
203dpi print resolution  
USB and Serial connectivity  
P-touch Template, ESC/P, CPCL ZPL 2,  
EPL 2 and DPL emulations supported

**TD-4210D**

4 inch direct thermal desktop  
printer with fast print speeds



Direct thermal print technology  
Print width of up to 104.1mm  
Print speeds up to 203.2mm/sec (8ips)  
203dpi print resolution  
USB and Serial connectivity  
P-touch Template, ESC/P, CPCL ZPL 2,  
EPL 2 and DPL emulations supported

**TD-4410D**

4 inch direct thermal desktop  
printer with fast print speeds and  
wired LAN



Direct thermal print technology  
Print width of up to 104.1mm  
Print speeds up to 203.2mm/sec (8ips)  
203dpi print resolution  
USB, Serial and Wired LAN connectivity  
P-touch Template, ESC/P, CPCL ZPL 2,  
EPL 2 and DPL emulations supported

**TD-4420DN**

High resolution 4 inch direct  
thermal desktop printer with  
wired LAN



Direct thermal print technology  
Print width of up to 108.4mm  
Print speeds up to 152mm/sec (6ips)  
300dpi print resolution  
USB, Serial and Wired LAN connectivity  
P-touch Template, ESC/P, CPCL ZPL 2,  
EPL 2 and DPL emulations supported

**TD-4520DN**

High resolution 4 inch direct  
thermal desktop printer with  
full connectivity



Direct thermal print technology  
Print width of up to 108.4mm  
Print speeds up to 152mm/sec (6ips)  
300dpi print resolution  
USB, Serial, Wired LAN, Bluetooth and  
WiFi connectivity  
Mono backlit LCD display  
P-touch Template, ESC/P, CPCL ZPL 2,  
EPL 2 and DPL emulations supported

**TD-4550DNWB**

## TD-4D linerless

Optimised for efficiency with sustainability in mind - linerless label printers.

4 inch direct thermal linerless desktop label printer with cutter



Direct thermal print technology

Print width of up to 104.1mm

Print speeds up to 203.2mm/sec (8ips)

203dpi print resolution

USB, Serial, Wired LAN connectivity

P-touch Template, ESC/P, Raster and ZPL 2, EPL 2, CPCL and DPL emulations supported

Pre-installed cutter with label-taken sensor

**TD-4420DNFC**

4 inch direct thermal linerless desktop label printer with full connectivity and cutter



Direct thermal print technology

Print width of up to 108.4mm

Print speeds up to 152.4mm/sec (6ips)

300dpi print resolution

USB, USB Host, Serial Bluetooth, Wired LAN and WiFi connectivity

P-touch Template, ESC/P, Raster and ZPL 2, EPL 2, CPCL and DPL emulation supported

Pre-installed cutter with label-taken sensor

**TD-4550DNWBFC**



## TD-4T range

High performance, thermal desktop printing for ultimate productivity.

**4 inch thermal transfer desktop printer**



Direct thermal and thermal transfer print technology

Print width of up to 108mm

Print speeds up to 152mm/sec

203dpi print resolution

USB, USB Host, Serial and Wired LAN connectivity

FBPL-EZD (EPL 2, ZPL 2, DPL) emulations supported

**TD-4420TN**

**High resolution 4 inch thermal transfer desktop printer**



Direct thermal and thermal transfer print technology

Print width of up to 105.7mm

Print speeds up to 127mm/sec

300dpi print resolution

USB, USB Host, Serial and Wired LAN connectivity

FBPL-EZD (EPL 2, ZPL 2, DPL) emulations supported

**TD-4520TN**

**4 inch thermal transfer desktop printer with fast print speeds, Bluetooth and WiFi**



Direct thermal and thermal transfer print technology

Print width of up to 108mm

Print speeds up to 203.2mm/sec

203dpi print resolution

USB, USB Host, Serial, Wired LAN, Bluetooth and WiFi connectivity

LCD display

FBPL-EZD (EPL 2, ZPL 2, DPL) emulations supported

**TD-4650TNWB**

**High resolution 4 inch thermal transfer desktop printer with Bluetooth and WiFi**



Direct thermal and thermal transfer print technology

Print width of up to 105.7mm

Print speeds up to 152.4mm/sec

300dpi print resolution

USB, USB Host, Serial, Wired LAN, Bluetooth and WiFi connectivity

LCD display

FBPL-EZD (EPL 2, ZPL 2, DPL) emulations supported

**TD-4750TNWB**

**4 inch thermal transfer desktop printer with fast print speeds, Bluetooth, WiFi and RFID support**



Direct thermal and thermal transfer print technology

Print width of up to 108mm

Print speeds up to 203.2mm/sec

203dpi print resolution

USB, USB Host, Serial, Wired LAN, Bluetooth and WiFi connectivity

LCD display

FBPL-EZD (EPL 2, ZPL 2, DPL) emulations supported

RFID media supported

**TD-4650TNWBR**

**High resolution 4 inch thermal transfer desktop printer with Bluetooth, WiFi and RFID support**



Direct thermal and thermal transfer print technology

Print width of up to 105.7mm

Print speeds up to 152.4mm/sec

300dpi print resolution

USB, USB Host, Serial, Wired LAN, Bluetooth and WiFi connectivity

LCD display

FBPL-EZD (EPL 2, ZPL 2, DPL) emulations supported

RFID media supported

**TD-4750TNWBR**

# TD-2D accessories

## Power and additional options

### PA-LP-008 Label peeler

TD-2320D203  
TD-2320D300  
TD-2350D203  
TD-2350D300  
TD-2320DSA203  
TD-2320DSA300  
TD-2350DSA203  
TD-2350DSAH300



### PA-CU-007 Cutter

TD-2320D203  
TD-2320D300  
TD-2350D203  
TD-2350D300  
TD-2320DSA203  
TD-2320DSA300  
TD-2350DSA203  
TD-2350DSAH300



### PA-KU-001 Keyboard unit

TD-2320DSA203  
TD-2320DSA300  
TD-2350DSA203  
TD-2350DSAH300



### PA-BB-004 Battery base\*

TD-2320D203  
TD-2320D300  
TD-2350D203  
TD-2350D300  
TD-2320DSA203  
TD-2320DSA300  
TD-2350DSA203  
TD-2350DSAH300

\* Requires PA-BT-004



### PA-HU2-002 Thermal print head (203dpi)

TD-2310D203  
TD-2320D203  
TD-2320D300  
TD-2350D203  
TD-2350D300  
TD-2320DSA203  
TD-2320DSA300  
TD-2350DSA203  
TD-2350DSAH300



### PA-HU3-002 Thermal print head (300dpi)

TD-2310D203  
TD-2320D203  
TD-2320D300  
TD-2350D203  
TD-2350D300  
TD-2320DSA203  
TD-2320DSA300  
TD-2350DSA203  
TD-2350DSAH300



### PA-PR2-002 Platen roller (203dpi)

TD-2310D203  
TD-2320D203  
TD-2320D300  
TD-2350D203  
TD-2350D300  
TD-2320DSA203  
TD-2320DSA300  
TD-2350DSA203  
TD-2350DSAH300



### PA-PR3-002 Platen roller (300dpi)

TD-2310D203  
TD-2320D203  
TD-2320D300  
TD-2350D203  
TD-2350D300  
TD-2320DSA203  
TD-2320DSA300  
TD-2350DSA203  
TD-2350DSAH300



### PA-BC-004 Battery charger

TD-2320D203  
TD-2320D300  
TD-2350D203  
TD-2350D300  
TD-2320DSA203  
TD-2320DSA300  
TD-2350DSA203  
TD-2350DSAH300



### PA-SCA-002 Serial cable

TD-2310D203  
TD-2320D203  
TD-2320D300  
TD-2350D203  
TD-2350D300  
TD-2320DSA203  
TD-2320DSA300  
TD-2350DSA203  
TD-2350DSAH300



### PA-BT-004 Li-ion rechargeable battery\*

TD-2310D203  
TD-2320D203  
TD-2320D300  
TD-2350D203  
TD-2350D300  
TD-2320DSA203  
TD-2320DSA300  
TD-2350DSA203  
TD-2350DSAH300



\* Requires PA-BB-004

### PA-AD-005(EU) Standard AC adapter

TD-2310D203  
TD-2320D203  
TD-2320D300  
TD-2350D203  
TD-2350D300  
TD-2320DSA203  
TD-2320DSA300  
TD-2350DSA203  
TD-2350DSAH300



### PA-AD-006(EU) Healthcare AC adapter

TD-2310D203  
TD-2320D203  
TD-2320D300  
TD-2350D203  
TD-2350D300  
TD-2320DSA203  
TD-2320DSA300  
TD-2350DSA203  
TD-2350DSAH300



# TD-4D accessories

## TD-4D Additional Options

### PA-LP-002 Label peeler

TD-4210D  
TD-4410D  
TD-4420DN  
TD-4520DN  
TD-4550DNWB



### PA-CU-001 Cutter

TD-4210D  
TD-4410D  
TD-4420DN  
TD-4520DN  
TD-4550DNWB



### PA-HU2-001 Thermal print head (203dpi)

TD-4210D  
TD-4410D  
TD-4420DN



### PA-HU3-001 Thermal print head (300dpi)

TD-4520DN  
TD-4550DNWB



### PA-PR2-001 Platen roller (203dpi)

TD-4210D  
TD-4410D  
TD-4420DN



### PA-PR3-001 Platen roller (300dpi)

TD-4520DN  
TD-4550DNWB



### PA-LCU-002 Linerless cutter

TD-4420DNFC  
TD-4550DNWBFC



### PA-LPR2-002 Linerless platen roller (203dpi)

TD-4420DNFC



### PA-LPR3-002 Linerless platen roller (300dpi)

TD-4550DNWBFC



### PA-AD-006 (EU) Healthcare AC adapter

TD-4210D  
TD-4410D  
TD-4420DN  
TD-4520DN  
TD-4550DNWB  
TD-4420DNFC  
TD-4550DNWBFC



## Why choose Brother?

### 3 years return-to-base warranty

We feel it's extremely important to make sure expert help is at hand when things go wrong. That's why we offer a three-year return-to-base warranty as standard with all of our thermal printers.

### "At your side"

Our award-winning specialist support team is on standby to offer support and advice for any integration needs. We also have Brother sales representatives across Europe and the rest of the world who are easy to contact and happy to help.

### The print experts

From our versatile range of multifunction printers, scanners and label printers, to our business solutions that help personalise your technology to suit your business needs, we pride ourselves on being "the print experts" and having a print solution for any application.

# TD-2D range

## brief summary

| TD-2310D203 | TD-2320D203 | TD-2320D300 | TD-2350D203 | TD-2350D300 |
|-------------|-------------|-------------|-------------|-------------|
| 2 Inch      |             |             |             |             |

### Printing

|                       |                                             |                                            |        |        |        |
|-----------------------|---------------------------------------------|--------------------------------------------|--------|--------|--------|
| Print technology      | Direct thermal                              |                                            |        |        |        |
| Print resolution      | 203dpi                                      | 203dpi                                     | 300dpi | 203dpi | 300dpi |
| Print speed           | 152.4mm/sec (6ips)                          |                                            |        |        |        |
| Max print width       | 59mm                                        |                                            |        |        |        |
| Min print length      | 6.4mm                                       |                                            |        |        |        |
| Max print length      | 3000mm                                      |                                            |        |        |        |
| Media sensor type     | Gap (Transmissive), Black mark (Reflective) |                                            |        |        |        |
| Media sensor location | Gap (fixed), Reflective (adjustable)        |                                            |        |        |        |
| Release mode          | Continuous, tear off                        | Continuous, tear off / Optional: peel, cut |        |        |        |

### Connectivity

|               |                                            |               |   |                                                                                   |
|---------------|--------------------------------------------|---------------|---|-----------------------------------------------------------------------------------|
| USB           | USB Ver.2.0 (Full Speed) (Type C)          |               |   |                                                                                   |
| USB Host Port | —                                          | Yes           |   |                                                                                   |
| Serial        | Original serial cable (option: PA-SCA-002) |               |   |                                                                                   |
| Bluetooth     | —                                          | —             | — | Yes. Bluetooth Ver 5.2 (BR/EDR: Class1, BLE: Class1.5) / MFi                      |
| Wireless LAN  | —                                          | —             | — | IEEE802.11 a/b/g/n (Infrastructure Mode)<br>IEEE802.11 g/n (Wireless Direct mode) |
| Wired LAN     | —                                          | 10/100BASE-TX |   |                                                                                   |

### General

|                          |                                                                                                           |        |        |                                     |        |
|--------------------------|-----------------------------------------------------------------------------------------------------------|--------|--------|-------------------------------------|--------|
| Dimensions (mm)          | 119 (w) x 224 (d) x 158 (h)                                                                               |        |        |                                     |        |
| Weight                   | 1.46kg                                                                                                    | 1.50kg | 1.50kg | 1.53kg                              | 1.53kg |
| Control panel            | 3 button / 3 LED                                                                                          |        |        | 7 button / 3 LED / Monochrome LCD   |        |
| Operating system support | Microsoft Windows 10,11<br>Microsoft Windows Server 2016,2019,2022<br>Linux                               |        |        |                                     |        |
| Supported commands       | Raster<br>ESC/P<br>P-touch Template / ZPL 2 emulation<br>CPCL emulation / EPL 2 emulation / DPL emulation |        |        |                                     |        |
| Mobile OS                | Android 9 or later                                                                                        |        |        | Android 9 or later, iOS 15 or later |        |

# TD-2D range

## brief summary

TD-2320DSA203

TD-2320DSA300

TD-2350DSA203

TD-2350DSAH300

2 Inch

### Printing

|                       |                                             |        |        |        |
|-----------------------|---------------------------------------------|--------|--------|--------|
| Print technology      | Direct thermal                              |        |        |        |
| Print resolution      | 203dpi                                      | 300dpi | 203dpi | 300dpi |
| Print speed           | 152.4mm/sec (6ips)                          |        |        |        |
| Max print width       | 59mm                                        |        |        |        |
| Min print length      | 6.4mm                                       |        |        |        |
| Max print length      | 3000mm                                      |        |        |        |
| Media sensor type     | Gap (Transmissive), Black mark (Reflective) |        |        |        |
| Media sensor location | Gap (fixed), Reflective (adjustable)        |        |        |        |
| Release mode          | Continuous, tear off / Optional: peel, cut  |        |        |        |

### Connectivity

|               |                                            |   |                                                                                   |
|---------------|--------------------------------------------|---|-----------------------------------------------------------------------------------|
| USB           | USB Ver.2.0 (Full Speed) (Type C)          |   |                                                                                   |
| USB Host Port | Yes                                        |   |                                                                                   |
| Serial        | Original serial cable (option: PA-SCA-002) |   |                                                                                   |
| Bluetooth     | —                                          | — | Yes. Bluetooth Ver 5.2<br>(BR/EDR: Class1, BLE: Class1.5) / MFi                   |
| Wireless LAN  | —                                          | — | IEEE802.11 a/b/g/n (Infrastructure Mode)<br>IEEE802.11 g/n (Wireless Direct mode) |
| Wired LAN     | 10/100BASE-TX                              |   |                                                                                   |

### General

|                          |                                                                                                           |        |                                     |                             |
|--------------------------|-----------------------------------------------------------------------------------------------------------|--------|-------------------------------------|-----------------------------|
| Dimensions (mm)          | 119 (w) x 224 (d) x 176 (h)                                                                               |        |                                     | 153 (w) x 280 (d) x 176 (h) |
| Weight                   | 1.77kg                                                                                                    | 1.77kg | 1.77kg                              | 1.94kg                      |
| Control panel            | 24 button / 3.5" colour touch screen                                                                      |        |                                     |                             |
| Operating system support | Microsoft Windows 10,11<br>Microsoft Windows Server 2016,2019,2022<br>Linux                               |        |                                     |                             |
| Supported commands       | Raster<br>ESC/P<br>P-touch Template / ZPL 2 emulation<br>CPCL emulation / EPL 2 emulation / DPL emulation |        |                                     |                             |
| Mobile OS                | Android 9 or later                                                                                        |        | Android 9 or later, iOS 15 or later |                             |

# TD-4D range

## brief summary

|               |        |
|---------------|--------|
| TD-4550DNWBFC | 4 Inch |
| TD-4420DNFC   |        |
| TD-4550DNWB   |        |
| TD-4520DN     |        |
| TD-4420DN     |        |
| TD-4410D      |        |
| TD-4210D      |        |

## Printing

| Print technology      | Direct thermal                             |                     |        |                     |        |                                                |                        |
|-----------------------|--------------------------------------------|---------------------|--------|---------------------|--------|------------------------------------------------|------------------------|
| Print resolution      | 203dpi                                     | 203dpi              | 203dpi | 300dpi              | 300dpi | 203dpi                                         | 300dpi                 |
| Print speed           | 127mm/sec<br>(5ips)                        | 203mm/sec<br>(8ips) |        | 152mm/sec<br>(6ips) |        | 203.2 mm/sec<br>(8ips)                         | 152.4 mm/sec<br>(6ips) |
| Max print width       | 104.1mm                                    |                     |        | 108.4mm             |        | 104.1mm                                        | 108.4mm                |
| Min print length      | 6.4mm                                      |                     |        |                     |        |                                                |                        |
| Max print length      | 3,000mm                                    |                     |        |                     |        |                                                |                        |
| Media sensor type     | Gap (transmissive), Bar (reflective)       |                     |        |                     |        | Gap (Transmissive),<br>Black mark (Reflective) |                        |
| Media sensor location | Gap (fixed), Reflective (adjustable)       |                     |        |                     |        |                                                |                        |
| Release mode          | Continuous, tear off / Optional: peel, cut |                     |        |                     |        | Standard: Cut                                  |                        |

## Connectivity

| USB           | USB Ver.2.0 (Full Speed) (Type B) |     |     |     |     |     |     |
|---------------|-----------------------------------|-----|-----|-----|-----|-----|-----|
| USB Host Port | —                                 | —   | —   | —   | Yes | —   | Yes |
| Serial        | Yes                               | Yes | Yes | Yes | Yes | Yes | Yes |
| Bluetooth     | —                                 | —   | —   | —   | Yes | —   | Yes |
| Wireless LAN  | —                                 | —   | —   | —   | Yes | —   | Yes |
| Wired LAN     | —                                 | —   | Yes | Yes | Yes | Yes | Yes |

## General

|                          |                                                                                                              |                                                                                            |                |                                                                             |                |
|--------------------------|--------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|----------------|-----------------------------------------------------------------------------|----------------|
| Dimensions (mm)          | 180 (w) x 224 (d) x 155 (h)                                                                                  |                                                                                            |                | 180 (w) x 255 (d) x 155 (h)                                                 |                |
| Weight                   | 2.08kg                                                                                                       |                                                                                            |                | 2.49kg                                                                      |                |
| Control panel            | 3 button 3 LED                                                                                               |                                                                                            | 7 button 3 LED | 3 button 3 LED                                                              | 7 button 3 LED |
| Operating system support | Windows<br>7/8/8.1/10/11,<br>Linux                                                                           | Windows 7/8/8.1/10/11,<br>Windows Server 2008/2008R2/2012/<br>2012R2/2016/2019/2022, Linux |                | Microsoft Windows10,11<br>Microsoft Windows Server<br>2016/2019/2022, Linux |                |
| Supported commands       | Raster<br>ESC/P<br>P-touch Template<br>ZPL 2 emulation<br>CPCL emulation<br>EPL 2 emulation<br>DPL emulation |                                                                                            |                |                                                                             |                |

# TD-4T range

## brief summary

|           |           |             |             |              |              |
|-----------|-----------|-------------|-------------|--------------|--------------|
| TD-4420TN | TD-4520TN | TD-4650TNWB | TD-4750TNWB | TD-4650TNWBR | TD-4750TNWBR |
| 4 Inch    |           |             |             |              |              |

### Printing

|                       |                                                         |           |                                                                                                                                                        |             |                                   |             |
|-----------------------|---------------------------------------------------------|-----------|--------------------------------------------------------------------------------------------------------------------------------------------------------|-------------|-----------------------------------|-------------|
| Print technology      | Thermal Transfer/Direct Thermal                         |           |                                                                                                                                                        |             |                                   |             |
| Print speed           | 152mm/sec                                               | 127mm/sec | 203.2mm/sec                                                                                                                                            | 152.4mm/sec | 203.2mm/sec                       | 152.4mm/sec |
| Resolution            | 203dpi                                                  | 300dpi    | 203dpi                                                                                                                                                 | 300dpi      | 203dpi                            | 300dpi      |
| Max print width       | 108mm                                                   | 105.7mm   | 108mm                                                                                                                                                  | 105.7mm     | 108mm                             | 105.7mm     |
| Min print length      | Peeler: 25.4mm,<br>Cutter: 25.4mm<br>Tear: 50mm         |           | Continuous: 5mm<br>Tear mode: Media width less than 2 inch: 25.4mm<br>Media width greater than 2 inch: 50mm<br>Peeler mode: 25.4mm Cutter mode: 25.4mm |             |                                   |             |
| Max print length      | 25,400mm                                                | 11,430mm  | 25,400mm                                                                                                                                               | 11,430mm    | 25,400mm                          | 11,430mm    |
| Media sensor type     | Gap (transmissive), Bar (reflective)                    |           |                                                                                                                                                        |             |                                   |             |
| Media sensor location | Gap (fixed), Reflective (adjustable)                    |           |                                                                                                                                                        |             |                                   |             |
| Tear off release mode | Standard: Continuous, Tear off Optional: Peeler, Cutter |           |                                                                                                                                                        |             | Standard:<br>Continuous, tear off |             |

### Connectivity

|               |     |     |     |     |     |     |
|---------------|-----|-----|-----|-----|-----|-----|
| USB           | Yes | Yes | Yes | Yes | Yes | Yes |
| Serial        | Yes | Yes | Yes | Yes | Yes | Yes |
| Wired LAN     | Yes | Yes | Yes | Yes | Yes | Yes |
| USB Host Port | Yes | Yes | Yes | Yes | Yes | Yes |
| Bluetooth     | —   | —   | Yes | Yes | Yes | Yes |
| Wireless LAN  | —   | —   | Yes | Yes | Yes | Yes |

### Connectivity

|                          |                                                                                                                                                  |                                                                                                                                                              |     |     |     |
|--------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|-----|-----|
| Dimensions (mm)          | 204 (w) x 280 (d) x 164 (h)                                                                                                                      | 219 (w) x 284 (d) x 191 (h)                                                                                                                                  |     |     |     |
| Weight                   | 2.5kg                                                                                                                                            | 2.5kg                                                                                                                                                        |     |     |     |
| Control panel            | 1 button 1 LED with 3 colours                                                                                                                    | 1 LED with 3 colors. 6 buttons for Navigation                                                                                                                |     |     |     |
| LCD                      | —                                                                                                                                                | Yes                                                                                                                                                          | Yes | Yes | Yes |
| Operating system support | Windows 7/8/8.1/10/11<br>Windows Server 2008/2008R2/2012/2012R2/2016<br><br>OS X 10.10.x,10.11.x<br>macOS 10.12.x, 10.13.x, 10.14.x, 11<br>Linux | Windows 7<br>Windows 8<br>Windows 8.1<br>Windows 10<br>Windows 11<br><br>Windows Server 2008, 2008 R2, 2012, 2012 R2, 2016, 2019<br>Linux<br>Mac OS v10.6-11 |     |     |     |
| Supported commands       | FBPL-EZD<br>(EPL 2, ZPL 2, DPL) emulation                                                                                                        |                                                                                                                                                              |     |     |     |



## TD-2D desktop printing supplies

| Supply type | Part code        | Description             | Size          | Quantity     | Rolls/Box |
|-------------|------------------|-------------------------|---------------|--------------|-----------|
| Receipt     | BDL-7J000058-102 | Continuous receipt roll | 58mm x 101.6m | n/a          | 8         |
| Labels      | BDE-1J026051-102 | Die-cut labels roll     | 51mm x 26mm   | 1,900 labels | 16        |

## TD-4D desktop printing supplies

| Supply type       | Part code        | Description               | Size            | Quantity     | Rolls/Box |
|-------------------|------------------|---------------------------|-----------------|--------------|-----------|
| Receipt           | BDL-7J000102-058 | Continuous receipt roll   | 101.6mm x 32.2m | n/a          | 20        |
|                   | BDL-7J000076-066 | Continuous receipt roll   | 76mm x 42m      | n/a          | 8         |
|                   | BDL-7J000058-102 | Continuous receipt roll   | 58mm x 101.6m   | n/a          | 8         |
|                   | BDL-7J000058-040 | Continuous receipt roll   | 58mm x 13.8m    | n/a          | 24        |
| Labels            | BDE-1J000102-102 | Continuous label roll     | 102mm x 58m     | n/a          | 8         |
|                   | BDE-1J050102-102 | Die-cut label roll        | 102mm x 50mm    | 1,050 labels | 8         |
|                   | BDE-1J152102-058 | Die-cut label roll        | 102mm x 152mm   | 85 labels    | 20        |
|                   | BDE-1J152102-102 | Die-cut label roll        | 102mm x 152mm   | 350 labels   | 8         |
|                   | BDE-1J026076-102 | Die-cut label roll        | 76mm x 26mm     | 1,900 labels | 8         |
|                   | BDE-1J044076-066 | Die-cut label roll        | 76mm x 44mm     | 400 labels   | 8         |
|                   | BDE-1J026051-102 | Die-cut label roll        | 51mm x 26mm     | 1,900 labels | 16        |
|                   | BDE-1J026051-060 | Die-cut label roll        | 51mm x 26mm     | 500 labels   | 12        |
| Linerless Labels* | BFA-274039-102   | Continuous linerless roll | 39mm x 82.3m    | N/A          | 12        |
|                   | BFA-274058-080   | Continuous linerless roll | 58mm x 51.8m    | N/A          | 32        |
|                   | BFA-274080-080   | Continuous linerless roll | 80mm x 51.8m    | N/A          | 32        |
|                   | BFA-274106-080   | Continuous linerless roll | 106mm x 51.8m   | N/A          | 9         |

\* Linerless Labels only compatible with TD-4420DNFC & TD-4550DNWBFC

# TD-4T desktop printing supplies

| Supply type | Part code        | Description                              | Size          | Quantity     | Rolls/Box |
|-------------|------------------|------------------------------------------|---------------|--------------|-----------|
| Labels      | BUS-1J074102-121 | Uncoated thermal transfer die cut labels | 102mm x 74mm  | 1,100 labels | 6         |
|             | BUS-1J150102-121 | Uncoated thermal transfer die cut labels | 102mm x 150mm | 550 labels   | 6         |
|             | BCS-1J074102-121 | Coated thermal transfer die cut labels   | 102mm x 74mm  | 1,100 labels | 6         |
|             | BCS-1J150102-121 | Coated thermal transfer die cut labels   | 102mm x 150mm | 550 labels   | 6         |
| Ribbons     | BWS-1D300-060    | Standard wax ribbon                      | 60mm x 300m   | n/a          | 12        |
|             | BWS-1D300-080    | Standard wax ribbon                      | 80mm x 300m   | n/a          | 12        |
|             | BWS-1D300-110    | Standard wax ribbon                      | 110mm x 300m  | n/a          | 12        |
|             | BWP-1D300-060    | Premium wax ribbon                       | 60mm x 300m   | n/a          | 12        |
|             | BWP-1D300-080    | Premium wax ribbon                       | 80mm x 300m   | n/a          | 12        |
|             | BWP-1D300-110    | Premium wax ribbon                       | 110mm x 300m  | n/a          | 12        |
|             | BSS-1D300-060    | Standard wax/resin ribbon                | 60mm x 300m   | n/a          | 12        |
|             | BSS-1D300-080    | Standard wax/resin ribbon                | 80mm x 300m   | n/a          | 12        |
|             | BSS-1D300-110    | Standard wax/resin ribbon                | 110mm x 300m  | n/a          | 12        |
|             | BSP-1D300-060    | Premium wax/resin ribbon                 | 60mm x 300m   | n/a          | 12        |
|             | BSP-1D300-080    | Premium wax/resin ribbon                 | 80mm x 300m   | n/a          | 12        |
|             | BSP-1D300-110    | Premium wax/resin ribbon                 | 110mm x 300m  | n/a          | 12        |
|             | BRS-1D300-060    | Standard resin ribbon                    | 60mm x 300m   | n/a          | 12        |
|             | BRS-1D300-080    | Standard resin ribbon                    | 80mm x 300m   | n/a          | 12        |
|             | BRS-1D300-110    | Standard resin ribbon                    | 110mm x 300m  | n/a          | 12        |
|             | BRP-1D300-060    | Premium resin ribbon                     | 60mm x 300m   | n/a          | 12        |
|             | BRP-1D300-080    | Premium resin ribbon                     | 80mm x 300m   | n/a          | 12        |
|             | BRP-1D300-110    | Premium resin ribbon                     | 110mm x 300m  | n/a          | 12        |

For additional consumable options please contact your local Brother office.

