

TJ Series **Durable industrial label printers**

The industrial label printer range specifications

Keep up with increasing demand with Brother's range of reliable 4 and 6 inch width industrial label printers – Built for you and built to last.

Print more than 1,000 labels a day with the TJ series, offering two print resolutions and print speeds of up to 14ips. In addition, there are a range of LED, LCD and touch panel displays to choose from, all designed with the user in mind.

Durable industrial label printer with LED indicator



Printer status LED indicator

203dpi resolution

Up to 6ips print speed

Print width of up to 107mm

FBPL-EZD (EPL2, ZPL2, DPL) supported

USB, USB Host, Serial, Ethernet and optional Wi-Fi*

TJ-4005DN

Durable industrial label printer with LED indicator



Printer status LED indicator

203dpi resolution

Up to 10ips print speed

Print width of up to 107mm

FBPL-EZD (EPL2, ZPL2, DPL) supported

450m ribbon capacity

USB, USB Host, Serial, Ethernet and optional Wi-Fi*

TJ-4020TN

Durable, high-resolution industrial label printer with LED indicator



Printer status LED indicator

300dpi resolution

Up to 7ips print speed

Print width of up to 105.7mm

FBPL-EZD (EPL2, ZPL2, DPL) supported

450m ribbon capacity

USB, USB Host, Serial, Ethernet and optional Wi-Fi*

TJ-4120TN

Durable industrial label printer with touch panel display



Touch panel display

203dpi resolution

Up to 10ips print speed

Print width of up to 107mm

FBPL-EZD (EPL2, ZPL2, DPL) supported

450m ribbon capacity

USB, USB Host, Serial, Ethernet and optional Wi-Fi*

TJ-4021TN



Durable, high-resolution industrial label printer with touch panel display



Touch panel display

300dpi resolution

Up to 7ips print speed

Print width of up to 105.7mm

FBPL-EZD (EPL2, ZPL2, DPL) supported

450m ribbon capacity

USB, USB Host, Serial, Ethernet and optional Wi-Fi*

TJ-4121TN

Super fast and durable industrial label printer with LCD display



LCD display

203dpi resolution

Up to 14ips print speed

Print width of up to 104mm

FBPL-EZD (EPL2, ZPL2, DPL) supported

600m ribbon capacity

USB, USB Host, Serial, Ethernet and optional Wi-Fi and Bluetooth*

TJ-4420TN

High quality, fast and durable industrial label printer with LCD display



LCD display

300dpi resolution

Up to 12ips print speed

Print width of up to 104mm

FBPL-EZD (EPL2, ZPL2, DPL) supported

600m ribbon capacity

USB, USB Host, Serial, Ethernet and optional Wi-Fi and Bluetooth*

TJ-4520TN

Super fast and durable industrial label printer with touch panel display and internal rewinder



Internal rewinder

Touch panel display

203dpi resolution

Up to 14ips print speed

Print width of up to 104mm

FBPL-EZD (EPL2, ZPL2, DPL) supported

600m ribbon capacity

USB, USB Host, Serial, Ethernet and optional Wi-Fi and Bluetooth*

TJ-4422TN

Why would a customer want an internal rewinder?

The internal rewinder enables users to print as many labels as needed, for use whenever required. The labels are instantly rewound as they print into a neat roll inside the printer, ensuring no mess is created and the printed label roll is ready to be collected when needed.

* Wi-Fi and Bluetooth connectivity options are purchased separately



High quality, fast and durable industrial label printer with touch panel display and internal rewinder



Internal rewinder

Touch panel display

300dpi resolution

Up to 12ips print speed

Print width of up to 104mm

FBPL-EZD (EPL2, ZPL2, DPL) supported

450m ribbon capacity

USB, USB Host, Serial, Ethernet and optional Wi-Fi and Bluetooth*

TJ-4522TN

TJ Industrial label printers.

Strong dependable

Strong dependable label printers for wider 6 inch labels



Reliable 6 inch industrial label printer for rapid printing



Touch panel display

203dpi resolution

Up to 12ips print speed

Print width of up to 168mm

FBPL-EZD (EPL2, ZPL2, DPL) supported

450m ribbon capacity

USB, USB Host, Serial, Ethernet and optional Wi-Fi and Bluetooth*

TJ-6421TN

Professional industrial 6 inch label printing at the best print quality



Touch panel display

300dpi resolution

Up to 10ips print speed

Print width of up to 168mm

FBPL-EZD (EPL2, ZPL2, DPL) supported

450m ribbon capacity

USB, USB Host, Serial, Ethernet and optional Wi-Fi and Bluetooth*

TJ-6521TN

Brother's 6 inch Industrial label printers, are the label printers to increase operational efficiency, suitable for SSCC pallet labelling, large shelf edge ID codes or parts manufacturing. These label printers can be configured with multiple options to flex to your business needs.

^{*} Wi-Fi and Bluetooth connectivity options are purchased separately

4 Inch

Accessories

PA-CU-004 * Cutter

TJ-4005DN TJ-4020TN TJ-4120TN TJ-4021TN TJ-4121TN



TJ-4420TN TJ-4520TN

PA-LP-005 * Peeler

TJ-4005DN TJ-4020TN TJ-4120TN TJ-4021TN TJ-4121TN



TJ-4420TN TJ-4520TN





PA-WI-002 WLAN Interface (WiFi)

TJ-4005DN TJ-4020TN TJ-4120TN TJ-4021TN TJ-4121TN



TJ-4422TN TJ-4522TN



BPA-HA2L-004 *

Thermal Print Head (203 dpi)

TJ-4005DN TJ-4020TN TJ-4021TN




BPA-HA2M-004 *



BPA-HA3L-004 *

Thermal Print

Head (300 dpi)



TJ-4520TN TJ-4522TN



TJ-4005DN TJ-4020TN TJ-4120TN TJ-4021TN TJ-4121TN



TJ-4420TN TJ-4520TN TJ-4422TN TJ-4522TN













6 Inch

Accessories

PA-CU-008 * Cutter

TJ-6421TN TJ-6521TN



PA-LP-009 * Peeler

TJ-6421TN TJ-6521TN



PA-RW-001 * Internal Rewinder 5 inch OD

TJ-6421TN TJ-6521TN



PA-WB-001 Dual Interface (WiFi and Bluetooth)

TJ-6421TN TJ-6521TN



PA-GP-003 * GPIO interface

TJ-6421TN TJ-6521TN



TJ Series

brief summary

	TJ-4420TN	TJ-4520TN	TJ-4422TN	TJ-4522TN	TJ-6421TN	TJ-6521TN	
	TJ Series - 4 Inch				6 Inch		
Printing							
Print technology	Direct Thermal and Thermal Transfer						
Print resolution	203dpi	300dpi	203dpi	300dpi	203dpi	300dpi	
Print speed	14 ips (356mm/sec)	12 ips (305mm/sec)	14 ips (356mm/sec)	12 ips (305mm/sec)	12 ips (305mm/sec)	10 ips (254mm/sec)	
Max print width		104mm		168mm			
Max print length	25400mm	11,430mm	25,400mm	11,430mm	14,732mm	6,604mm	
Min print length		5mm			10mm		
Media sensor type	Gap transmissive (position adjustable), Black mark reflective (position adjustable), Head open transmissive, Ribbon encoder reflective, Ribbon end transmissive		Gap transmissive (position adjustable), Black mark reflective (position adjustable), Head open transmissive, Ribbon encoder reflective, Ribbon end transmissive, Media near end		Gap (transmissive), Black mark (reflective), Head open (transmissive), Ribbon encoder (reflective), Ribbon end (transmissive)		
Media sensor location		Adjustable: Gap, Black mark, Fixed: Ribbon encoder, Ribbon end, Head open TJ-4005DN: Adjustable: Gap, Black mark, Fixed: Head open			Adjustable: Gap, Black mark, Fixed: Ribbon encoder, Ribbon end, Head open		
Release mode	Standard: Cont Optional: F	inuous, Tear off Peeled, Cut	Standard: Continuous, Rewinding		Standard: Continuous, Tear off Optional: Peeled, Cut, Rewind		
Connectivity							
USB	•	•	•	•	•	•	
USB host	•	•	•	•	•	•	
Serial	•	•	•	•	•	•	
Bluetooth (option)*	•	•	•	•	•	•	
Wired LAN	•	•	•	•	•	•	
Wireless LAN (option)	•	•	•	•	•	•	
General							
Dimensions (mm)	276mm (W) x 326mm (H) x 502mm (D)		276mm (W) x 412mm (H) x 502mm (D)		357mm (W) x 313mm (H) x 510mm (D)		
Weight	15.35kg Peeler mode: 16.4kg Cutter mode: 16.9kg		18.93kg		17.9kg		
Control panel	LCD display, 1 status indicator, 6 button navigation		Colour touch display, 1 status indicator, 6 button navigation		Colour touch display, 1 status indicator, 6 button navigation		
Touch panel			•	•	•	•	
Tear bar	•	•			•	•	
Operating system support		Windows, Linux, MacOS, Android and iOS					
Supported Command		FBPL-EZD (EPL2,ZPL2,DPL)					

 $^{^{\}star}$ Bluetooth connectivity option is part of the same single module with Wireless LAN.