

Durable and easy to integrate

The industrial label printer range at a glance

Keep up with increasing demand with Brother's range of reliable industrial label printers – built for you and built to last.

Print more than 1,000 labels a day with the TJ series, offering two print resolutions and print speeds of up to 14ips. In addition, there are a range of LED, LCD and touch panel displays to choose from, all designed with the user in mind.

Durable industrial label printer with LED indicator



Printer status LED indicator

203dpi resolution

Up to 6ips print speed

Print width of up to 107mm

FBPL-EZD (EPL2, ZPL2, DPL) supported

USB, USB Host, Serial, Ethernet and optional WiFi *

TJ-4005DN

Durable industrial label printer with LED indicator



Same as TJ-4005DN plus

Up to 10ips print speed

450m ribbon capacity

TJ-4020TN

Durable industrial label printer with touch panel display



Same as TJ-4020TN plus

Touch panel display

TJ-4021TN

Durable, high-resolution industrial label printer with LED indicator



Printer status LFD indicator

300dpi resolution

Up to 7ips print speed

Print width of up to 105.7mm

FBPL-EZD (EPL2, ZPL2, DPL) supported

450m ribbon capacity

USB, USB Host, Serial, Ethernet and optional WiFi *

TJ-4120TN

Durable, high-resolution industrial label printer with touch panel display



Same as TJ-4120TN plus

Touch panel display

TJ-4121TN



Super fast and durable industrial label printer with LCD display



LCD display

203dpi resolution

Up to 14ips print speed

Print width of up to 104mm

FBPL-EZD (EPL2, ZPL2, DPL) supported

600m ribbon capacity

USB, USB Host, Serial, Ethernet and optional WiFi and Bluetooth *

TJ-4420TN

Super fast and durable industrial label printer with touch panel display and internal rewinder



Same as TJ-4420TN plus

Internal rewinder

Touch panel display

TJ-4422TN

High quality, fast and durable industrial label printer with LCD display



LCD display

300dpi resolution

Up to 12ips print speed

Print width of up to 104mm

FBPL-EZD (EPL2, ZPL2, DPL) supported

600m ribbon capacity

USB, USB Host, Serial, Ethernet and optional WiFi and Bluetooth *

TJ-4520TN

High quality, fast and durable industrial label printer with touch panel display and internal rewinder



Same as TJ-4520TN plus

Internal rewinder

Touch panel display

TJ-4522TN

Why would a customer want an internal rewinder?

The internal rewinder enables users to print as many labels as needed, for use whenever required. The labels are instantly rewound as they print into a neat roll inside the printer, ensuring no mess is created and the printed label roll is ready to be collected when needed.

TJ Accessories

PA-CU-004 * Cutter	PA-CU-005 * Cutter	PA-LP-005 *
TJ-4005DN TJ-4020TN TJ-4120TN TJ-4021TN TJ-4121TN	TJ-4420TN TJ-4520TN	TJ-4005DN TJ-4020TN TJ-4120TN TJ-4021TN TJ-4121TN

BPA-HA2M-004 *

Thermal Print

TJ-4420TN

TJ-4422TN

Head (203 dpi)





PA-WI-002 WLAN Interface (WiFi)

TJ-4005DN TJ-4020TN TJ-4120TN TJ-4021TN TJ-4121TN



PA-WB-001

Dual Interface (WiFi and Bluetooth)

TJ-4420TN TJ-4520TN TJ-4422TN TJ-4522TN





BPA	-HA	\2L-	004	*

Thermal Print Head (203 dpi)

TJ-4005DN TJ-4020TN TJ-4021TN

mmm

BPA-HA3L-004 *

Thermal Print Head (300 dpi)

TJ-4120TN TJ-4121TN



BPA-HA3M-004 *

Thermal Print Head (300 dpi)

TJ-4520TN TJ-4522TN



BPA-PRL-004 *

Platen Roller

TJ-4005DN TJ-4020TN TJ-4120TN TJ-4021TN TJ-4121TN



BPA-PRM-004 *

Platen Roller

TJ-4420TN TJ-4520TN TJ-4422TN TJ-4522TN





^{*} Dealer installable only.

TJ Series

brief summary

	TJ-4005DN	TJ-4020TN	TJ-4120TN	TJ-4021TN	TJ-4121TN	TJ-4420TN	TJ-4520TN	TJ-4422TN	TJ-4522TN	
					TJ Serie	s				
Printing										
Print technology	Direct Thermal	Di	rect Thermal and T	hermal Transfer		Direct Thermal and Thermal Transfer				
Print resolution	203dpi	203dpi	300dpi	203dpi	300dpi	203dpi	300dpi	203dpi	300dpi	
Print speed	6 ips (152mm/sec)	10 ips (254mm/sec)	7 ips (178mm/sec)	10 ips (254mm/sec)	7 ips (178mm/sec)	14 ips (356mm/sec)	12ips (305mm/sec)	14 ips (356mm/sec)	12ips (305mm/sec)	
Max print width	107mm	107mm	105.7mm	107mm	105.7mm		104mm	1		
Max print length	25400mm	25400mm	11430mm	25400mm	11430mm	25400mm	11430mm	25400mm	11430mm	
Min print length			5mm			5mm				
Media sensor type	• `	Gap (transmissive), Black mark (reflective), Ribbon encoder (reflective), Ribbon end (transmissive), Head open (transmissive) TJ-4005DN: Gap (transmissive), Black mark (reflective), Head open (transmissive)				Gap transmissive (position adjustable), Black mark reflective (position adjustable), Head open transmissive, Ribbon encoder reflective, Ribbon end transmissive Gap transmissive (position adjustable), Black mark reflective (position adjustable), Head open transmissive, Ribbon encoder reflective, Ribbon end transmissive, Media near end			ck mark reflective able), Head open Ribbon encoder end transmissive,	
Media sensor location		Adjustable: Gap, Black mark, Fixed: Ribbon encoder, Ribbon end, Head open TJ-4005DN: Adjustable: Gap, Black mark, Fixed: Head open				Adjustable: Gap, Black mark, Fixed: Ribbon encoder, Ribbon end, Head open				
Release mode		Standard: Continuous, Tear off Optional: Peeled, Cut			Standard: Continuous, Tear off Optional: Peeled, Cut Standard: Continuous, rewinding					
Connectivity										
USB	•	•	•	•	•	•	•	•	•	
USB host	•	•	•	•	•	•	•	•	•	
Serial	•	•	•	•	•	•	•	•	•	
Bluetooth (option)*						•	•	•	•	
Wired LAN	•	•	•	•	•	•	•	•	•	
Wireless LAN (option)	•	•	•	•	•	•	•	•	•	
General										
Dimensions (mm)		248mm (W) x 274mm (H) x 4	36mm (D)		276mm (W) x 326mm (H) 276mm (W) x 412mm (H) x 502mm (D) x 502mm (D)				
Weight	9.2kg Peeler mode: 9.9kg Cutter mode: 9.6kg Gross weight: 11.2kg			Peeler mo Cutter mo	lkg de: 10.1kg de: 9.8kg jht: 11.4kg	Peeler mod	15.35kg Peeler mode: 16.4kg Cutter mode: 16.9kg		18.93kg	
Control panel	4 intuitive icon indicators, 1 status indicator, 2 buttons (pause, feed)			1 status	r touch display, indicator, navigation	LCD display, Colour touc 1 status indicator, 1 status i 6 button navigation 6 button n		indicator,		
Touch panel				•	•			•	•	
Tear bar	•	•	•	•	•	•	•			
Operating system support	Windows, Linux, MAC, Android and iOS									
Supported Command		FBPL-EZD (EPL2,ZPL2,DPL)			FBPL-EZD (EPL2,ZPL2,DPL)					

 $^{^{\}star}$ Bluetooth connectivity option is part of the same single module with Wireless LAN.