Specialist tape cassettes

In addition to the extensive range of TZe tapes in various colours and sizes, specialist tapes for industrial use have been developed for specific labelling tasks.

Flexible-ID Tape

Use on: Curved surfaces or itself



- Wrapping/flagging individual wires
- Sharp bends
- Cylindrical surfaces

Strong Adhesive Tape

Use on: Uneven, rough and textured surfaces



- Painted metal
- Powder-coated surfaces
- Utility cabinets

Heat-shrink tube

Use on: Wires and cables



- Shrinks and grips cable when heat is applied
- Permanent
- Durable

Technical Specifications

Items included

Hardware

PT-E300 labelling machine

Lithium-ion battery

AC adapter

18mm black on yellow strong adhesive laminated

label cassette (8m) User guide

Wrist strap Carry case

740g

Housing dimensions (mm) 133 (w) x 220 (h) x 74 (d)

Housing weight

Tape size/type TZe tape: 3.5, 6, 9, 12, 18mm

Print resolution 180 dpi

Max. print height 15.8mm

Max. print speed 20mm / sec

Cutter type Manual: Cutter blade

Keyboard type PC style with numeric keypad

Number of keys

LCD display 15 characters x 3 line graphic

LCD backlight

LCD size 67mm x 40mm

Print preview

Text buffer Max. 200 chrs

Label memory 50 memory locations with up to 2,400

Yes

characters total

Lithium-ion battery (supplied)
AC adapter (supplied)

6 x AA (LR6/HR6) alkaline batteries

(not supplied)

Built-in software

Built-in fonts Built-in symbols

Font styles

Frames

-in symbols

Character sizes 7: (6, 9, 12, 18, 24, 36, 42 pt)
Character widths 3: (extended, medium, condensed)

9

Underline
Max. number of lines

Horizontal alignment

Automatic length labels: left aligned

Pre-set label length: centre aligned

Tape length setting Yes (25-300mm)
Tape margin setting Narrow, half, full, chain print

Tab function

Specialist labelling functions

Cable wrap, cable flag, face place, sequential numbering, patch panel, punch block

Yes

Automatic numbering Yes
Mirror printing No
Vertical printing Yes

Barcode creation Yes: (CODE39, CODE 128, EAN13, EAN8, ITF 2/5, UPC-A, UPC-E, CODABAR, GS1-128/UCC/EAN128)

Copy (repeat) printing

Yes: (1-9)

Print preview

Yes: (graphic preview)

Auto power off

Unit change Yes: (inch/mm)
Language change 20 languages:

20 languages: (English, German, French, Spanish, Portuguese, Italian, Dutch, Danish, Norwegian, Swedish, Finnish, Hungarian, Czech, Polish, Romanian, Slovenian, Slovakian, Croatian, Turkish, Brazilian Portuguese)

Contact:

Power



Brother International Europe Tame Street, Audenshaw Manchester, M34 5JE United Kingdom









Industrial Labelling Machine

With dedicated functions for common labelling applications, easily create durable labels for faceplates, cables, consumer units and other electrical and datacom installations.

www.brother.eu

- Large backlit graphic display
- Dedicated function keys to easily create labels
- Includes tape cassette, AC adapter and carry case
- Prints 3.5, 6, 9, 12 & 18mm labels







P-touch E300VP

The P-touch E300VP is an indispensible tool for all electricians and datacom installers and comes complete with a lithium-ion rechargeable battery and AC adapter, all housed in a durable carry case. The large backlit graphic LCD, standard PC style keyboard and specialised functions have been developed to make common industrial labelling tasks quick and easy. Leave a professional impression by creating high quality durable labels for your installations.



Includes common electrical, datacom,

Include barcodes for added AV, security and safety symbols.

P-touch laminated labels – designed to last

Brother P-touch laminated TZe tapes are available in many different colours and sizes. The thermal transfer ink is sandwiched between two protective layers of PET (polyester film), protecting the text against the effects of liquids, abrasion, temperature, chemicals and sunlight. As the labels have been tested to the extreme, you can be confident of a professional quality label that has been designed to last.



9 barcode protocols

security and safety.

















384 built-in symbols