PJ-700 Series






PJ-700 Series A4 Mobile Printer Range

These compact mobile printers offer a durable 'in the field' mobile printing solution for sales/service, logistics and public safety/emergency services officials. Bluetooth, Wi-Fi and USB connections conveniently link to smartphones, tablets, PDA's and laptops.



- A4 sized printing in a compact design
- Fast print speed 8ppm
- High quality print resolution up to 300 dpi
- Direct thermal no ink or toner needed
- Powered by rechargeable batteries or AC adapter/vehicle power adapters
- Multiple connection methods available including Bluetooth, Wireless Direct, Wi-Fi and USB



Why choose a mobile printer from Brother?

In the modern business climate, companies today are striving to differentiate themselves from the competition and are therefore investing in technologies which will increase worker productivity and improve customer satisfaction. Mobile printers are now being recognised as an integral part of the overall mobile mix, due to the many benefits they offer to field workers and their overall Return On Investment (ROI).

The benefits of printing on the move...

- Increased efficiency, freedom and mobility
- Reduced office administration costs
- Increased customer confidence with on-site printouts
- Greater accuracy reducing human error
- Valuable business tool for closing deals instantly



Vertical markets & applications

Field Sales

Exceed customer expectations by using the PJ-700 series printer while on the move or on site. Busy field sales professionals are able to print whatever is required at the their customers' premises without having to communicate back to the office, giving them more time to visit other customers.



Field Service

Mobile engineers are able to increase efficiency and accuracy by leaving hard copies of documents while on the move, and reduce the risk of any future queries.

Logistics & Deliveries

Print a wide range of documents while on the road, in the truck or at your customer's premises. The fast print speed is ideal for busy delivery drivers with hectic schedules.



Invoices

- Order forms
- Delivery notes
- Stock data
- Guarantees

Applications:

- Citations & fines
- Patient reports
- Incident reports
- Warning notices

Emergency Services

The PJ-700 series printers have become increasingly popular in the emergency services for a variety of applications. When used together with the vehicle mount & car charger, they have proved to be the perfect in-vehicle solution for the Police, Ambulance and Fire Services on a global scale. By printing medical documents and penalty fines on demand they can reduce the risk of clerical errors saving officers and medical staff valuable time.



Applications:

- Invoices
- Service reports
- Quotations
- Parts & labour
- Diagnostics

Invoices

Applications:

- Reports
- Quotations
- Contracts
- Terms & conditions
- Financial planning

PJ-700 series In detail

Thermal print technology

When investigating the options for mobile technology, key decision makers are increasingly considering thermal printers as the only true and reliable solution for field professionals. Printers using advanced direct thermal technology produce an image by heating specially coated thermal paper. When the paper passes over the thermal print head, the coating turns black in the areas where it is heated, producing an image. Thermal printing is increasingly considered by many as the only realistic solution for mobile applications for a number of reasons:

- Lets busy mobile workers to be able to focus on the job at hand without the inconvenience, or the added cost of purchasing ink, toner or ribbons.
- No downtime due to ink, toner or ribbons running out, and being unable to source replacements quickly.
- Enables the machine to be mounted however required, in any orientation, and can also be carried around without the risk of spillages, leaks and smudges.
- Less susceptibility to fluctuating seasonal temperatures and humidity extremes compared to other mobile technologies.





Software support and features

Brother can provide the necessary tools required for software developers to integrate the print function into their mobile app. Printer drivers are available for Windows[®] OS, and Software Development Kits can be provided to support Apple iOS, Android and Windows[®] Mobile applications. To see more information visit: **www.brother.eu/developers**





Direct thermal printing offers the most reliable technology for mobile printing solutions

Seamless connections with Bluetooth, Wi-Fi, USB and communications to other devices At just 26 cm wide and weighing approximately 480g (excluding battery), the PJ-700 series offers a true A4 mobile solution that fits easily into a briefcase or computer bag, and can be mounted in vehicles or other work areas. A4 size is considered ideal for printing documents where more detailed information is required, such as invoices, service reports and delivery notes. There is also a full range of accessories available, allowing the PJ-700 series to be fully customised as needed.

Further features include...

- Basic Imaging Protocol (BIP) support for downloading and printing JPEG files
- The ability to store document overlays in the printer to minimise data transfers
- Fully featured design software for creating & downloading the document overlays
- PJ ESC/P printer language offers compatibility with a variety of embedded systems





Choice of power options including Li-ion rechargeable battery, AC adapters or vehicle power kits



Durable, and dependable. The PJ-700 series has been designed for reliable printing in many environments





Compact, lightweight design for ultimate portability

Use A4 cut sheet paper or continuous paper rolls. Simply tear the paper once printed

PJ-700 series. Build your own customised print solution

Step 1: Choose your printer

Model Comparison	PJ-722	PJ-723	PJ-762	PJ-763	PJ-763MFi	PJ-773
USB		1				
Bluetooth interface			 ✓ 		 Image: A start of the start of	
Wi-Fi (Adhoc/Infrastructure/Wireless Direct)						
203 x 200 dpi print resolution						
300 x 300 dpi print resolution		\checkmark		\checkmark	 Image: A start of the start of	
Template download/printing mode	 ✓ 	 ✓ 	\checkmark	 ✓ 		
ESC/P and Brother command modes		\checkmark	\checkmark	\checkmark		
MFi						

Step 2: Choose your power options

PA-BT-002 Li-ion rechargeable battery	PA-AD-600EU AC adapter (EU)	PA-AD-600UK AC adapter (UK)	PA-CD-600CG 12V car adapter (cigarette socket)	PA-CD-600WR 12V car adapter (permanently wired)

Step 3: Choose your case and mounting option

PA-RH-600	PA-RB-001	PA-RC-001	PA-CC-500	PA-CM-500
Paper roll holder	Protective cover	Roll printer case	Carry case	Car mounting kit

Step 4: Choose your paper

PA-R-410	PA-C-411
A4 paper roll	A4 cut sheet paper
0	Street Hilling of the street o



Specifications

ITERACESUSB Ver.2.0 (ull speed) type A to min' type B (pritter)33.0 bothN/AN/AVer.2.1+EDR OPP and HOPP suppriedVer.2.1+EDR OPP and HOPP suppriedN/A30.0 bothN/AN/AN/AVer.2.1+EDR OPP and HOPP suppriedVer.2.1+EDR OPP and HOPP suppriedN/AWreless-LANN/AN/AN/AN/AN/AVer.2.1+EDR OPP and HOPP suppriedVer.2.1+EDR OPP and HOPP sup	PRINTING	PJ-722	PJ-723	PJ-762	PJ-763	PJ-763MFi	PJ-773		
Naming speed Image logent leaded Image logent leaded environment() [1] Import field method 204.2mm 208.8mm	Print resolution	203 x 200dpi	300 x 300dpi	203 x 200dpi	300 x 300dpi	300 x 300dpi	300 x 300dpi		
kaper feed methodUUU </td <td>Print technology</td> <td></td> <td colspan="7">Direct thermal</td>	Print technology		Direct thermal						
Interfact204.2mm208.2mm208.2mm208.8mm208.8mm208.8mm208.8mmis. of pages per battery chargePectargeable L-Ion Dattery - approximately 600 obertsNTERFACESSS-USB Ver2.20 full apeed type A terminity bye B (printersNaN/AN/AN/AN/ANueboothN/AN/AN/AN/ANueboothN/AN/AN/AN/AN/AN/AN/AN/AN/AN/AEEB82 : Thigh (Mortes orice)freedees-LANN/AN/AN/AN/AN/AEEB82 : Thigh (Mortes orice)freedees-LANN/AN/AN/AN/AN/AEEB82 : Thigh (Mortes orice)freedees-LAN securityN/AN/AN/AN/AN/AEEB82 : Thigh (Mortes orice)freedees-LAN securityN/AN/AN/AN/AN/AEEB82 : Thigh (Mortes orice)freedees-LAN securityN/AN/AN/AN/AN/AEEB82 : Thigh (Mortes orice)freedees-LAN securityN/AN/AN/AN/AN/AN/AEEB82 : Thigh (Mortes orice)freedees-LAN securityN/AN/AN/AN/AN/AN/AEEB82 : Thigh (Mortes orice)freedees-LAN securityN/AN/AN/AN/AN/AN/AN/AEEB82 : Thigh (Mortes orice)freedees-LAN securityN/AN/AN/AN/AN/AN/AN/AN/AN/AN/Afreedees-LAN security<	Printing speed		Ave.: 8ppm (under Brother standard environment) [1]						
An of pages per battery charge Rechargeable L-lon Battery: approximately 600 ohets (1.5%) printing duty and using at Lily charged new battery) NTERFACES USB Wr.2.0 full speed, type A to minit type B (printing- type 100° printing duty and using at Lily charged new battery) Ver.2.1+EDR Ver.2.1+E	aper feed method				Manual paper	feed			
ITERACES USB VIE2.0 [full speed] type A to mol type B (printer) Issebuoth N/A N/A N/A Vie2.1 =EDR Vie2.1 =EDR Vie2.1 =EDR N/A Uireless-LAN N/A N/A N/A N/A N/A N/A N/A IEEE802.11 log in (finational mode) in the set of the s	Print width	204.2mm	208.8mm	204.2mm	208.8mm	208.8mm	208.8mm		
JBB UBENDER USB VER 2.0 (kull speed) kype A to mini kype B (printler) Skuetooth NAA NAA NAA VI.2.1+EDR Class 2.5 PP, BP, OPP (ALTON DATE) Wireless-LAN NAA NAA NAA NAA NAA NAA NAA NAA NAA	No. of pages per battery charge			0	, ,,	,			
Buetooth NA NA NA NA VPC 2.1-ECR Class 2.SPP, BP, OPP and NCPP an	INTERFACES								
Image: Control HCRP supported Class 25, PR Pr. OPP and HCRP supported Class 21, Not And Pr. And Pr	ISB			USB Ver.2.0	(full speed) type A t	to mini type B (printe	r)		
Image: Section of the section of t	Bluetooth	N/A	N/A	OPP and HCRP supported Class 2 SPP OPP, HCRP		Class 2 SPP, BIP, OPP, HCRP and	N/A		
Image: Second Lange Second	Wireless-LAN	N/A	N/A	N/A	N/A	N/A			
lili-in fonts Bitmap font: Helsinki, Brussel, Letter Gothic Bold Outline font: Helsinki, Brussel, Letter Gothic Bold Outline font: Helsinki, Brussel, Letter Gothic Bold Outline font: Helsinki, Brussel, Letter Gothic sex arcode support Yes EMPLATE/FORM STORAGE EMPLATE/FORM STORAGE Itemary size (RAM/Flash/User) 32MB / 32MB / 32MB / 6MB EMERAL Immensions 255(W) x 55(D) x 30(H) mm /eight excl battery & paper 480g (approx) attery Rechargeable Li-ion Battery 10.8V (optional accessory) C adapter AC adapter 15 V (optional accessory) C adapter Cigarette lighter plug or permanently wired (optional accessories) perating system support Windows® Vistar/7/8/8.1/10 Windows® Server 2008/2008 R2; Windows® Server 2012/2012 R2 - Mac OS X v 10.8/10.9/10.10 - Lim tobie OS Android - USB Android Mondows® Server 2012/2012 R2 - Mac OS X v 10.8/10.9/10.10 - Lim tobie OS Android - USB Android On Android//OS ENTRONMENTAL Emperature -10°C to +50°C (during operation) / -20°C to +60°C (during storage) undity 20% to 80% (no condensation - during operation and storage) uto power off Yes: 15 settings ONTENTS (PJ-722 / PJ-723 / PJ-762 / PJ-763 / PJ-763/PJ-773), Quick setup guide,	Wireless-LAN Security	N/A	N/A	N/A	N/A	N/A	<pre>< Personal mode > Open System (None/WEP) Public Key Authentication (WEP) WPA-PSK/WPA2-PSK (TKIP/AES) < Enterprise mode > LEAP (CKIP) EAP-FAST (TKIP/AES) PEAP (TKIP/AES) EAP-TTLS (TKIP/AES) EAP-TLS (TKIP/AES) EAP-TLS (TKIP/AES) ADHOC MODE Open System (None/WEP) WIRELESS DIRECT</pre>		
Outline tont: Helsinki, Brussel, Letter Gothic ont sizes 10 cpi, 12 cpi, 15 cpi and proportional sizes arcode support Yes EMPLATE/FORM STORAGE Itemary size (RAM/Flash/User) 32MB / 32M	J ESC/P LANGUAGE	1	1		·	1			
Image: Constant of the second sec	uilt-in fonts								
EMPLATE/FORM STORAGE Itemory size (RAM/Flash/User) 32MB / 32MB / 32MB / 6MB EENERAL Itemensions //eight excl battery & paper 255(W) x 55(D) x 30(H) mm /eight excl battery & paper //eight excl battery & paper 480g (approx) attery Rechargeable Li-ion Battery 10.8V (optional accessory) C adapter AC adapter 15 V (optional accessory) ar adapter Cigarette lighter plug or permanently wired (optional accessories) Iperating system support Windows® Vista/7/8/8.1/10 Windows® Server 2008/2008 R2; Windows® Server 2012/2012 R2 - Mac OS X v 10.8/10.9/10.10 - Lim Notice OS Android - USB Android NVIRONMENTAL -10°C to +50°C (during operation) / -20°C to +60°C (during storage) umidity 20% to 80% (no condensation - during operation and storage) uto power off Yes: 15 settings (PJ-722 / PJ-723 / PJ-763 / PJ-763 / PJ-773), Quick setup guide,	ont sizes		10 cpi, 12 cpi, 15 cpi and proportional sizes						
lemory size (RAM/Flash/User) 32MB / 32MB / 32MB / 6MB ENERAL Seteral Seteral Setera	arcode support		Yes						
IENERAL Impersions Jest Colspan="2">Jest Colspan="2" Jest	EMPLATE/FORM STORAGE								
imensions 255(W) x 55(D) x 30(H) mm /eight excl battery & paper 480g (approx) attery Rechargeable Li-ion Battery 10.8V (optional accessory) C adapter AC adapter 15 V (optional accessory) ar adapter Cigarette lighter plug or permanently wired (optional accessories) perating system support Windows® Vista/7/8/8.1/10 Windows® Server 2008/2008 R2; Windows® Server 2012/2012 R2 - Mac OS X v 10.8/10.9/10.10 - Linu tobile OS Android Android NVIRONMENTAL -10°C to +50°C (during operation) / -20°C to +60°C (during storage) umidity 20% to 80% (no condensation - during operation and storage) uto power off Yes: 15 settings ONTENTS (PJ-722 / PJ-723 / PJ-763 / PJ-763 / PJ-763 / PJ-773), Quick setup guide,	lemory size (RAM/Flash/User)				32MB / 32MB /	6MB			
Veight excl battery & paper 480g (approx) attery Rechargeable Li-ion Battery 10.8V (optional accessory) C adapter AC adapter 15 V (optional accessory) car adapter Cigarette lighter plug or permanently wired (optional accessories) uar adapter Windows® Vista/7/8/8.1/10 Windows® Server 2008/2008 R2; Windows® Server 2012/2012 R2 - Mac OS X v 10.8/10.9/10.10 - Line Nobile OS Android - USB Android NVIRONMENTAL -10°C to +50°C (during operation) / -20°C to +60°C (during storage) unidity undidity 20% to 80% (no condensation - during operation and storage) ves: 15 settings votretts (PJ-722 / PJ-723 / PJ-763 / PJ-763 / PJ-763 / PJ-773), Quick setup guide,	ENERAL								
attery Rechargeable Li-ion Battery 10.8V (optional accessory) C adapter AC adapter 15 V (optional accessory) ar adapter Cigarette lighter plug or permanently wired (optional accessories) perating system support Windows® Vista/7/8/8.1/10 Windows® Server 2008/2008 R2; Windows® Server 2012/2012 R2 - Mac OS X v 10.8/10.9/10.10 - Lint tobile OS Android - USB Android Android/iOS NVIRONMENTAL =noperature -10°C to +50°C (during operation) / -20°C to +60°C (during storage) unidity umidity 20% to 80% (no condensation - during operation and storage) Yes: 15 settings ONTENTS (PJ-722 / PJ-723 / PJ-762 / PJ-763 / PJ-763 MFi / PJ-773), Quick setup guide,	imensions				255(W) x 55(D) x 30	D(H) mm			
C adapter AC adapter 15 V (optional accessory) ar adapter Cigarette lighter plug or permanently wired (optional accessories) perating system support Windows® Vista/7/8/8.1/10 Windows® Server 2008/2008 R2; Windows® Server 2012/2012 R2 - Mac OS X v 10.8/10.9/10.10 - Lint tobile OS Android - USB Android Android/iOS NVIRONMENTAL emperature -10°C to +50°C (during operation) / -20°C to +60°C (during storage) unidity uuridity 20% to 80% (no condensation - during operation and storage) Yes: 15 settings ONTENTS (PJ-722 / PJ-763 / PJ-763 / PJ-763 / PJ-773), Quick setup guide,	/eight excl battery & paper		480g (approx)						
iar adapter Cigarette lighter plug or permanently wired (optional accessories) perating system support Windows® Vista/7/8/8.1/10 Windows® Server 2008/2008 R2; Windows® Server 2012/2012 R2 - Mac OS X v 10.8/10.9/10.10 - Linu Mobile OS Android - USB Android Android NVIRONMENTAL emperature -10°C to +50°C (during operation) / -20°C to +60°C (during storage) umidity 20% to 80% (no condensation - during operation and storage) uto power off Yes: 15 settings IONTENTS (PJ-722 / PJ-723 / PJ-762 / PJ-763 / PJ-763MFi / PJ-773), Quick setup guide,	attery		Rechargeable Li-ion Battery 10.8V (optional accessory)						
windows® Vista/7/8/8.1/10 Windows® Server 2008/2008 R2; Windows® Server 2012/2012 R2 - Mac OS X v 10.8/10.9/10.10 - Lint Mobile OS Android - USB Android Android/iOS NVIRONMENTAL -10°C to +50°C (during operation) / -20°C to +60°C (during storage) unidity umidity 20% to 80% (no condensation - during operation and storage) visc 15 settings contents (PJ-722 / PJ-723 / PJ-762 / PJ-763 / PJ-763 MFi / PJ-773), Quick setup guide,	C adapter		AC adapter 15 V (optional accessory)						
Android - USB Android Android Mobile OS Android - USB Android NVIRONMENTAL Image: Comparison of the state of the stat	ar adapter		Cigarette lighter plug or permanently wired (optional accessories)						
NVIRONMENTAL emperature -10°C to +50°C (during operation) / -20°C to +60°C (during storage) umidity 20% to 80% (no condensation - during operation and storage) uto power off Yes: 15 settings CONTENTS (PJ-722 / PJ-723 / PJ-762 / PJ-763 / PJ-763MFi / PJ-773), Quick setup guide,	perating system support	Windows [®] Vis	Windows® Vista/7/8/8.1/10 Windows® Server 2008/2008 R2; Windows® Server 2012/2012 R2 - Mac OS X v 10.8/10.9/10.10 - Linux						
emperature -10°C to +50°C (during operation) / -20°C to +60°C (during storage) umidity 20% to 80% (no condensation - during operation and storage) uto power off Yes: 15 settings ONTENTS (PJ-722 / PJ-723 / PJ-762 / PJ-763 / PJ-763MFi / PJ-773), Quick setup guide,	Nobile OS	Androi	d - USB	And	droid		Android/i0S		
umidity 20% to 80% (no condensation - during operation and storage) uto power off Yes: 15 settings ONTENTS (PJ-722 / PJ-723 / PJ-762 / PJ-763 / PJ-763MFi / PJ-773), Quick setup guide,	NVIRONMENTAL								
uto power off Yes: 15 settings ONTENTS (PJ-722 / PJ-763 / PJ-763 / PJ-763MFi / PJ-773), Quick setup guide,	emperature		-10°C to +50°C (during operation) / -20°C to +60°C (during storage)						
ONTENTS (PJ-722 / PJ-723 / PJ-762 / PJ-763 / PJ-763MFi / PJ-773), Quick setup guide,	umidity		20% to 80% (no condensation - during operation and storage)						
(PJ-722 / PJ-723 / PJ-763 / PJ-763 / PJ-763MFi / PJ-773), Quick setup guide,	uto power off		Yes: 15 settings						
	CONTENTS								

[1] Brother standard environment is based on using A4 size with JAITA J1 pattern at 23 degrees C via USB using AC adaptor or Li-ion battery

Contact:		

Brother International Europe Ltd

Brother House, 1 Tame Street, Audenshaw, Manchester M34 5JE Tel: +44(0)161 330 6531 Fax: +44(0)161 330 5520 Website: www.brother.eu

All specifications correct at time of printing. Brother is a registered trademark of Brother Industries Ltd. Brand product names are registered trademarks or trademarks of their respective companies.

