## **Specialist tape cassettes**

In addition to the extensive range of TZe tapes in various colours and sizes, specialist tapes for industrial use have been developed for specific labelling tasks.

#### Flexible-ID Tape

Use on: Curved surfaces or itself



- Wrapping/flagging individual wires
- Sharp bends
- · Cylindrical surfaces

#### **Strong Adhesive Tape**

Use on: Uneven, rough and textured surfaces



- Painted metal
- Powder-coated surfaces
- Utility cabinets

#### Heat-shrink tube

Use on: Wires and cables



- Shrinks and grips cable when heat is applied
- Permanent
- Durable

# **Technical Specifications**

#### Items included

PT-E300 labelling machine

Lithium-ion battery

AC adapter

18mm black on yellow strong adhesive laminated

label cassette (8m) User guide

Wrist strap Carry case

#### **Hardware**

133 (w) x 220 (h) x 74 (d) Housing dimensions (mm)

740g Housing weight

Tape size/type TZe tape: 3.5, 6, 9, 12, 18mm

Print resolution 180 dpi 15.8mm Max. print height 20mm / sec Max. print speed Manual: Cutter blade Cutter type PC style with numeric keypad Keyboard type

Number of kevs

LCD display 15 characters x 3 line graphic

Yes

LCD backlight LCD size

Print preview

Text buffer

Max. 200 chrs Label memory 50 memory locations with up to 2,400

characters total

Power Lithium-ion battery (supplied)

AC adapter (supplied)

67mm x 40mm

6 x AA (LR6/HR6) alkaline batteries

(not supplied)

#### **Built-in software**

Built-in fonts Built-in symbols

Character sizes Character widths 3: (extended, medium, condensed)

Font styles Frames

Underline Max. number of lines

Horizontal alignment Automatic length labels: left aligned

Tape length setting Tape margin setting

Tab function

Specialist labelling functions

Automatic numbering Mirror printing

Vertical printing Barcode creation

Copy (repeat) printing

Print preview Auto power off Unit change

Language change

7: (6, 9, 12, 18, 24, 36, 42 pt)

Pre-set label length: centre aligned Yes (25-300mm)

Narrow, half, full, chain print

Cable wrap, cable flag, face place, sequential numbering, patch panel, punch block

No

Yes: (CODE39, CODE 128, EAN13, EAN8, ITF 2/5, UPC-A, UPC-E, CODABAR, GS1-128/UCC/EAN128)

Yes: (1-9) Yes: (graphic preview) Yes

Yes: (inch/mm)

20 languages: (English, German, French, Spanish, Portuguese, Italian, Dutch, Danish, Norwegian, Swedish,

Finnish, Hungarian, Czech, Polish, Romanian, Slovenian, Slovakian, Croatian, Turkish, Brazilian Portuguese)

Contact



Brother International Corporation (Ireland) Ltd Boeing Road, Airways Ind Est, Santry, D.17, Tel: 01-2411900 Fax: 01-8424666 Web: www.brother.ie









# **Industrial Labelling Machine**

With dedicated functions for common labelling applications, easily create durable labels for faceplates, cables, consumer units and other electrical and datacom installations.

## www.brother.ie

- Large backlit graphic display
- Dedicated function keys to easily create labels
- Includes tape cassette, AC adapter and carry case
- Prints 3.5, 6, 9, 12 & 18mm labels







### P-touch E300VP

The P-touch E300VP is an indispensible tool for all electricians and datacom installers and comes complete with a lithium-ion rechargeable battery and AC adapter, all housed in a durable carry case. The large backlit graphic LCD, standard PC style keyboard and specialised functions have been developed to make common industrial labelling tasks quick and easy. Leave a professional impression by creating high quality durable labels for your installations.



## Includes common electrical, datacom,

Include barcodes for added AV, security and safety symbols.

## P-touch laminated labels – designed to last

Brother P-touch laminated TZe tapes are available in many different colours and sizes. The thermal transfer ink is sandwiched between two protective layers of PET (polyester film), protecting the text against the effects of liquids, abrasion, temperature, chemicals and sunlight. As the labels have been tested to the extreme, you can be confident of a professional quality label that has been designed to last.



9 barcode protocols

security and safety.

















384 built-in symbols