*P-touch* E550WVP

**brother** at your side

## Industrial PC labelling machine

Create durable labels for electrical or datacom installations, via the easy-to-use built-in labelling functions, PC software or from your smartphone or tablet with the Brother cable labelling app.

- Large backlit graphic display
- Advanced cutter for easy-to-peel labels
- Includes 2 tape cassettes, AC adapter, lithium-ion battery, USB cable, hand strap and carry case
- Prints 3.5, 6, 9, 12, 18 and 24mm labels

**www.brother.ie**

"Clear identification and safety are critical in my line of work, and being able to print durable labels from my PC or smartphone gives me total flexibility, whatever job I am on."



Mobile Cable Label Tool

240 VOLTS
ADD

Simple Label/
Heatshrink Tube

A-B01

Faceplate

A-B01

Cable Wrap

A-B01

Cable Flag

01 : 02 : 03 : 04

Patch Panel

Punch Down Block

Saved Labels/Print Log

P-touch

E550WVP

# P-touch E550WVP

Ensuring cables, conduits, switches and sockets are clearly identified with long lasting, durable labels is essential for electricians, datacom, telecom and security equipment installers. The Brother P-touch E550WVP creates labels that help address ANSI/EIA/TIA-606A/B, and that meet the UL-969 standards.

**Prints labels 3.5 to 24mm in width**
Print labels in various widths to suit any space

**Large backlit graphic LCD**
Easily view symbols and preview your label before printing

**Sequential numbering**
Print labels containing a sequence of numbers or letters

**384 built-in symbols**
Includes common electrical, datacom, AV, security and safety symbols

**Automatic label cutter with easy peel**
Keeps multiple labels in the correct order

**Specialist label functions**
Easily create general, faceplate, cable flag/wrap, patch panel and punch down block labels

**Database search/merge/print**
Upload data from your PC to print labels on-site

**USB & Wi-Fi**
Print from PC or mobile wirelessly

## P-touch laminated labels – designed to last

Brother P-touch laminated TZe tapes are available in many different colours and sizes. The thermal transfer ink is sandwiched between two protective layers of PET (polyester film), protecting the text against the effects of liquids, abrasion, temperature, chemicals and sunlight. As the labels have been tested to the extreme, you can be confident of a professional quality label that has been designed to last.

P-touch LABELS TESTED TO THE EXTREME

Laminated | Temperature Resistant | Water Resistant | Fade Resistant | Abrasion Resistant | Chemical Resistant | Easy Peel | Strong Adhesion

# Specialist tape cassettes

In addition to the extensive range of TZe tapes in various colours and sizes, specialist tapes for industrial use have been developed for specific labelling tasks.

### Flexible-ID Tape
Use on: Curved surfaces or itself



- Wrapping/flagging individual wires
- Sharp bends
- Cylindrical surfaces

### Strong Adhesive Tape
Use on: Uneven, rough and textured surfaces



- Painted metal
- Powder-coated surfaces
- Utility cabinets

### Heat-shrink tube
Use on: Wires and cables



- Shrinks and grips cable when heat is applied
- Permanent
- Durable

# Technical Specifications

## Main features

| | |
|---|---|
| Display type | 16 chrs x 3 lines backlit graphic LCD with print preview |
| Interfaces | USB 2.0, Wi-Fi, Wireless Direct |
| Print speed | 30mm / second (maximum) |
| Maximum tape width | 24mm |
| Maximum print height | 18mm |
| Cutter type | Automatic (Full & Half) |
| Battery type | BA-E001 Li-ion rechargeable battery (supplied) 6 x AA alkaline/rechargeable batteries (LR6/HR6 - not supplied) |

## Label creation

| | |
|---|---|
| Dedicated labelling functions | General ¦ Faceplate ¦ Patch panel ¦ Punch block ¦ Cable wrap ¦ Cable flag ¦ Heat shrink tube Serialise (automatic number incrementation) |
| Fonts | 14 fonts ¦ 10 styles ¦ 6 to 48 point size |
| Max. lines per label | 7 (on 24mm width tape cassette) |
| Max. text blocks | 99 |
| Symbols | 384 |
| Frames | 7 |
| Barcodes | 9 protocols |
| Automatic numbering | 1-99 |
| Copy printing | 1-99 |
| Vertical text printing | Yes |
| Rotated text printing | Rotate once ¦ Rotate and repeat |

## Memory

| | |
|---|---|
| Maximum characters per label | 1500 |
| Label memory locations | 99 |

## PC software main features

| | |
|---|---|
| Supported operating systems | Windows Vista®, Windows® 7, Windows® 8, Mac OS X 10.6 - 10.9 |
| Cable labelling wizard | Yes |
| Font faces | All installed true-type fonts |
| Font styles | 12 |
| Image import | JPG, BMP, TIFF and other popular types |
| Screen capture | Yes |
| Frames | 153 |
| Barcodes | 21 protocols including 1D/2D barcodes |

## Included items

| | |
|---|---|
| In the box | PT-E550 labelling machine 24mm black on yellow strong adhesive tape cassette (8m) 12mm black on white Flexible ID tape (8m) Li-ion rechargeable battery AC adapter Label design software and printer driver CD-ROM USB cable, wrist strap and user guide |

## Supplies

| | |
|---|---|
| Tape type ¦ Tape widths | TZe tape cassettes ¦ 3.5, 6, 9, 12, 18, 24mm HSe tube cassettes¦ 5.8, 8.8, 11.7, 17.7, 23.6mm |

## Optional accessories

| | |
|---|---|
| Batteries | BA-E001 Li-ion rechargeable battery AA alkaline/rechargeable batteries (LR6/HR6) |
| AC adapter | AD-E001 AC adapter |

## Weights & Dimensions

| | |
|---|---|
| PT-E550WVP | 126mm(w) x 250mm(h) x 94mm(d) ¦ 1.05kg |

Contact:

HSe TUBE  5.8mm 8.8mm 11.7mm 17.7mm 23.6mm

TZe TAPE  3.5mm 6mm 9mm 12mm 18mm 24mm